NORIX

SPECIFICATIONS



Model TOR40 Weight

*Intended for indoor use only

18 lbs

Dimensions

Overall Height 19.1"
Depth 20"
Overall Width 20"

Table Top 16.2"W x 18"D











DETAILS

Color

Harvest (light), Java (dark)

*Proprietary TruGrain™ aesthetic provides authentic texture and gradation that replicates natural wood. Variations in color and finish vary from product to product and lot to lot, just like natural wood. Due to differences in monitors, printers and materials, actual product colors may vary.

Options

Ganging kit, Bolt-down kit

Factory Ballasting (50 lbs)

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required

Installation

Required for ganging plates.

Fabrication & Material

One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation and contraband resistance. Contains a minimum of 30% recycled content.

Made in the U.S.A.

*March 2022: Due to current supply chain issues caused by Force Majeure, Toro may or may not have recycled content at this time.

Warranty

10 year limited replacement warranty

Maintenance

For routine and regular cleaning, Norix* recommends the use of Simple Green* or an equivalent cleaning product with a soft damp cloth. TruGrain products are suitable for use with hospital-grade disinfectants (such as Virex*, Wexcide* or Oxivir Five 16*) per manufacturers' instructions.

TESTING -

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

Performance Test Standards

- Tested to 750 lb static load
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012