# Titan<sup>®</sup> Bunkable Frame Style Bed - Steel Deck



# **SPECIFICATIONS**



## Model

TNT1611-0004 **Weight** 188 lbs

\*Intended for indoor use only

#### Dimensions

 Length
 86.5"

 Width
 56.5"

 Height
 37"

 Recommended Mattress

 54"x80"
 54"

# DETAILS

#### Color

Steel Color: Khaki, Ebony

<u>Optional Steel Colors</u>: Cream, London Fog,

Pewter, Shark, Slate, Irish Moss, Dusk, Mink \*Minimums apply

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### Options

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Bolt-down Kit, Bunk Lock Clamps, Glide kit

#### Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

## **Fabrication & Material**

Cut, formed, welded steel, powder coated steel

Bed deck: 12 gauge

End frame legs: 16 gauge

End frame cross-members: 16 gauge

Connector Brackets: 3/8" thick

End Caps: Injection molded high-impact plastic

<u>Optional Headboard:</u> 45 lb density M3 grade particle board with durable highpressure laminate surface and 2mm PVC edge (Wild Cherry Standard). Made in the U.S.A.

#### Installation

None required for standard model

## Warranty

10 year limited replacement warranty

## Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

<u>Optional Decorative Laminate:</u> Norix recommends the use of Simple Green<sup>®</sup> or an equivalent cleaning product.

# TESTING

## Environmental Test Standards

 GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
 Compliant with Healthian Heapitals

• Compliant with Healthier Hospitals guidelines

#### **Performance Test Standards**

Tested to 1,000 lb static load



